



- | | | |
|---------------------------|-------------------------------|-----------------------------|
| 1 Handle assembly | 30 Female screw | 55 Alarm selector washer |
| 2 Handle knob | 31 Clutch race plate | 57 Handle screw |
| 6 Handle shaft | 33a Liningless disk | 58 Handle washer |
| 7 Handle nut | 34 Duoble lined winged disk | 61 Slotted washer |
| 9 Handle slide plate | 35b1 Single lined winged disk | (2½/O 4/O 6/O only) |
| 12 Gear huosing | 36 Internal loc-spring ring | 62 Clutch bearing-lock ring |
| 14 Main gear | 37 Clutch taper spring | 63 Pawl spring |
| 14a Main gear bearing | 41 Alarm striker | 64 Self tapping screw |
| 14b Main gear bearing | 42 Upper frame post | 68a Ball bearing |
| 15 Anti reverse pawl | 43 Harness lug | 70 Alarm striker plate |
| 16a Pawl shaft | 43a External harness lug | 71 Alarm screw |
| 16b Pawl pin | 44 Cilindrical frame post | 73 Ball spacer ring |
| 17 Right side plate | 45 Reel stand frame post | 74 Spring |
| 18 Drag adjustable dial | 46 Reel stand | 75 Alarm selector |
| 20 Adjustable limit stop | 47 Rod clamp | 79 Striker springs |
| 21 Spool | 48 Clamp screw | 86 Ball |
| 22a Ball bearing | 49 Nut | 87 Screw |
| 23a Pinion gear | 50 Collar nut | 88 Centering pins |
| 24 Left side plate | 51 Male screw washer | 89 Allen screw |
| 25 Ball bearing washer | 52 Pressure Washer spring | 90 91 92Rod brace assembly |
| 28 Clutch adjusting lever | 53 Alarm selector cover | |
| 29 Male screw | 54 Spring-lock ring | |

